

SUPPLIERS OF PERSONAL INDUSTRIAL SAFETY

EQUIPMENT • CLOTHING • FOOTWEAR • HYGIENE PRODUCTS

- **9** 0121 544 5208
- 👨 www.provincialsafety.co.uk
- sales@provincialsafety.co.uk



UPDATED: 22/11/2018

Aquatek

Dual Coated Latex Glove

A premium fully coated flat latex glove on a soft 13gg nylon liner. There is an additional second foam latex coating for the palm which offers superb grip in dry and wet applications whilst maintaining excellent flexibility and comfort even after extended use. This glove is waterproof up to the cuff which makes it ideal for use in refuse collection or particularly wet applications.



FEATURES AND TECHNOLOGY















GENERAL PURPOSE









TYPICAL INDUSTRIES



UTILITIES

BUILDING & WASTE & AGRICULTURE PLUMBING CONSTRUCTION RECYCLING

TECHNICAL INFORMATION

ORDER REF#	G/AQUATEK	
COATING MATERIAL	DUAL COATED, LATEX, LATEX FOAM	
PACKING	PER PACK: 10	PER CASE: 120
SIZES AVAILABLE	8 (M), 9 (L), 10 (XL), 11 (2XL)	
EU TYPE CERTIFICATION BY	CTC, 4 rue Hermann Frenkel 69367 Lyon cedex 07 France (Notified Body No. 0075)	

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)



- ¹ 'X' denotes not tested.

 ² * Where applicable, EN388:2016 scores take precedent and are ongoing.

 ³ There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.







SUPPLIERS OF PERSONAL INDUSTRIAL SAFETY


EQUIPMENT • CLOTHING • FOOTWEAR • HYGIENE PRODUCTS

- 0121 544 5208
- www.provincialsafety.co.uk
- sales@provincialsafety.co.uk



UPDATED: 22/11/2018


CERTIFICATION LEGENDS





NEWTON LEVEL ≥ 30 ≥ 22 Ε ≥ 15 D ≥ 10 ≥ 5 в > 2

^{*} For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.





* For details regarding maximum permissable user exposure, see

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals, 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire, 5. Do not subject to high speed or serrated blades, 6. Always read enclosed user instructions before using these gloves, 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

WARNING: This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit: https://www.ultimateindustrial.co.uk/product/1035-Aquatek

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCi customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCi assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks or registered* trademarks of their respective holders. © UCI limited, 2018

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.