

Aquatek-Thermo

Thermal Dual Latex Coated Glove.

Premium thermal dual coated glove constructed from a 13 gauge polyester outer with a warm 10 gauge brushed loop acrylic inner to keep the hand warm whilst ensuring comfort. A full flat orange latex coating up to the wrist creates a liquid repellent barrier whilst the foam latex second coating maximises grip in wet and dry conditions. Tested contact cold and contact heat level 2 so perfect for protection against low or high temperatures. Anatomically shaped to mould to the hands natural resting shape.



FEATURES AND TECHNOLOGY



HEAT TESTED



COLD CONDITIONS PACKAGED



RETAIL



WATERPROOF



DUAL COATED



LATEX FOAM

TYPICAL INDUSTRIES



GENERAL PURPOSE



UTILITIES



OIL, GAS & MINING



LOGISTICS & WAREHOUSING



BUILDING & CONSTRUCTION

TECHNICAL INFORMATION

ORDER REF#	G/AQUATEK-THERMO
COATING MATERIAL	DUAL COATED, LATEX FOAM
PACKING	PER PACK: 10 PER CASE: 100
SIZES AVAILABLE	7 (S), 8 (M), 9 (L), 10 (XL), 11 (2XL)
EU TYPE CERTIFICATION BY	CTC, 4 rue Hermann Frenkel 69367 Lyon cedex 07 France (Notified Body No. 0075)

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

EN388:2016



2 2 3 2 X

Abraction (0-24)
Cut (0-5)
Tear (0-4)
Puncture (0-5)
TDM Cut (A-F)

EN407:2004



X 2 X X X X

Contact Heat

EN511:2006



X 2 X

Contact Cold (0-2)



¹ 'X' denotes not tested.

² * Where applicable, EN388:2016 scores take precedent and are ongoing.

³ There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.

CAT II  

CERTIFICATION LEGENDS



* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

NEWTON LEVEL

≥ 30	F
≥ 22	E
≥ 15	D
≥ 10	C
≥ 5	B
> 2	A



* For details regarding maximum permissible user exposure, see separate sheet.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit:
<https://www.ultimateindustrial.co.uk/product/1101-Aquatek-Thermo>

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered® trademarks of their respective holders. © UCI Limited, 2019