

# NESS+

## SPORTY LOOK

With Ness+ you enjoy all the benefits of the NESS model with added comfort thanks to co-injected temples. Exclusive Platinum® scratch and fog resistant coating helps you work more efficiently.

 PLATINUM®



  
28g



NESSPPSI




NESSPPSF



NESSPCSP



RUSHKITS (option)  
Strap

- + ULTRA-WRAPAROUND FRAME**
- + PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT**
- + PANORAMIC FIELD OF VISION**
- +  PLATINUM® (P) SCRATCH AND FOG RESISTANT COATING**
- + NON-SLIP NOSE BRIDGE**

**bolle**  
SAFETY

# NESS+

## SPORTY LOOK

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
NESS+	Clear	NESSPPSI	2C-1,2  1 FT KN €€	EN166 FT €€	Anti-scratch/Anti-fog
	CSP	NESSPCSP	5-1,4  1 FT KN €€	EN166 FT €€	Anti-scratch/Anti-fog
	Smoke	NESSPPSF	5-3,1  1 FT KN €€	EN166 FT €€	Anti-scratch/Anti-fog
	Strap only (option)	RUSHKITS	-	-	-

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

€€ European standard Manufacturer name

### TECHNOLOGIES

#### CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

#### PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### PACKAGING AND EAN13 CODE

	NESSPPSI	NESSPPSF	NESSPCSP	RUSHKITS
Individual plastic bag	3660740008543	3660740008550	3660740008567	3660740007546
10 safety spectacles per inner box	3660740108540	3660740108557	3660740108564	3660740107543
200 safety spectacles per outer pack	3660740208547	3660740208554	3660740208561	3660740207540

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 10
FRAME	-
TEMPLES	PC + TPR
BRIDGE	PVC
STRAP	Nylon/15mm/Adjustable
SPARE LENSES	No



Non-contractual pictures

26/02/2019

Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : uk@bollebrands.com

bolle-safety.com

**bolle**  
SAFETY