

# RUSH

## THE COMFORT OF PANORAMIC VISION

Available in twilight version, the panoramic and lightweight RUSH model offers perfect optical quality, permanent comfort and modern design.



RUSHPSI



RUSHPSF



RUSHDPI



RUSHTWI



\* RUSHKITFS  
Foam & Strap Kit (The  
foam is compatible with  
RUSH & RUSH+ Models  
// The strap is only com-  
patible with RUSH+)



25 g

### SUPPLIED WITH

Adjustable cord  
CORDC



**+ UPPER PROTECTION**













**+ ADJUSTABLE NON-SLIP BRIDGE**

**+ NON-SLIP TEMPLES**

**bollé**  
SAFETY

# RUSH

## THE COMFORT OF PANORAMIC VISION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH	 Clear	RUSHPSI	2C-1,2  1 FT €€	 EN166 FT €€	Anti-scratch/anti-fog
	 Smoke	RUSHPSF	5-3,1  1 FT €€	 EN166 FT €€	Anti-scratch/anti-fog
	 HD	RUSHDPI	2C-1,2  1 FT €€	 EN166 FT €€	Hydrophobic/anti-scratch
	 Twilight	RUSHTWI	5-2  1 FT €€	 EN166 FT €€	Anti-scratch/anti-fog
	* Foam & Strap Kit	RUSHKITFS	-	-	-

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:


€€ European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### TECHNOLOGY

#### BHD

A revolutionary coating for exceptional clarity and light transmission. Its visible light transmission rate is 96% compared with 90% for conventional clear lenses.

#### B-TWILIGHT

the new B-twilight technology offers the advantages of ESP with a double anti-fog coating (on both sides of the lenses) to prevent fogging in the most challenging conditions. Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. B-Twilight filters 76% of blue light.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE					
	RUSHDPI	RUSHPSI	RUSHPSF	RUSHTWI	RUSHKITFS
Individual plastic bag	3660740000097	3660740006648	3660740006655	3660740006662	3660740006488
10 safety spectacles per inner box	3660740100094	3660740106645	3660740106652	3660740106669	3660740106485
240 safety spectacles per outer pack	3660740200091	3660740206642	3660740206659	3660740206666	3660740206482

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC + PVC
STRAP	Non applicable
FOAM	SBR
SPARE LENSES	No



18/09/2014

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY