

SLAM

ULTRA-TRENDY

Stylish and easy-to-wear. The SLAM model provides protection at all times while offering unbeatable comfort.



23 g

SUPPLIED WITH

Adjustable cord
CORDC



SLAPSI



SLAPSF



SLAPSJ



SLAESP



SLAWPCC2



SLAWPCC3



SLAWPCC5










- + WRAP-AROUND FIT**
- + ALL-ROUND VISION**
- + COMFORTABLE STRAIGHT TEMPLES**

bolle
SAFETY

SLAM

ULTRA-TRENDY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SLAM	 Clear	SLAPSI	2C-1,2 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch/anti-fog
	 Smoke	SLAPSF	5-3,1 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch/anti-fog
	 Yellow	SLAPSJ	2C-1,2 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch/anti-fog
	 ESP	SLAESP	5-1,4 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch
	 Welding shade 1,7	SLAWPCC2	1,7 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch
	 Welding shade 3	SLAWPCC3	3 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch
	 Welding shade 5	SLAWPCC5	5 ☞ 1 FT CE	☞ EN166 FT CE	Anti-scratch

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

CE European standard ☞ Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
 - T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- CE European standard ☞ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

B-ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	SLAPSI	SLAPSF	SLAPSJ	SLAESP	SLAWPCC2	SLAWPCC3	SLAWPCC5
Individual plastic bag	3660740001087	3660740001094	3660740001100	3660740001117	3660740001124	3660740001131	3660740001148
10 safety spectacles per inner box	3660740101084	3660740101091	3660740101107	3660740101114	3660740101121	3660740101138	3660740101145
200 safety spectacles per outer pack	3660740201081	3660740201098	3660740201104	3660740201111	3660740201128	3660740201135	3660740201142

CHARACTERISTICS

LENSES	PC - 2,3 mm - Curve 11
FRAME	PC
TEMPLES	PC
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle-safety.com

bolle
SAFETY